


HYDRAULIC BOLT TENSIONER DEVICES

- ◆ Compact and reliable.
- ◆ Reduce the damage of the seals result from mishandling.
- ◆ One specification can suit various specifications of bolts.
- ◆ A groove is visible as the maximum piston extension is reached.
- ◆ Ability to link number of tensioners together.
- ◆ Detachable and interchangeable bridge components.
- ◆ Maximum tool operating pressure 1500 bar.
- ◆ Can match hand pump, electric pump.



Part No.	Bolt Size (mm)	Load (kn)	Dimension (mm)				Weight (kg)
			A	B	C	D	
GTS 1	3/4" - 10 UNC	230	75	64	46	73	2.3
	7/8" - 9 UNC		75	65	46	73	2.15
	1" - 8 UN		75	70	46	80	2.15
	1.1/8" - 8 UN		75	76	46	81	2.15
GTS 2	1.1/8" - 8 UN	450	104	83	56	94	5
	1.1/4" - 8 UN		104	86	56	96	4.8
	1.1/2" - 8 UN		104	92	56	101	4.9
GTS 3	1.1/2" - 8 UN	843.21	135	98	58	110	9.8
	1.5/8" - 8 UN		135	112	58	109	9.2
	1.7/8" - 8 UN		135	117	58	118	9.2
	2" - 8 UN		135	121	58	119	8.9
GTS 4	1.7/8" - 8 UN	1275.16	165	131	59	120	16.4
	2" - 8 UN		165	125	59	119	15.9
	2.1/4" - 8 UN		165	136	59	124	16
	2.1/2" - 8 UN		165	148	59	132	15.3
GTS 5	2.1/2" - 8 UN	1910.49	194	148	61	135	22.9
	2.3/4" - 8 UN		194	163	61	149	24.8
	3" - 8 UN		194	171	61	147	22.4
GTS 6	3.1/4" - 8 UN	2648.78	236	183	66	156	38.3
	3.3/4" - 8 UN		236	211	66	169	37.2
	4" - 8 UN		236	223	66	176	36.9